> Hydraulic

COMPACT 99T BP





DESCRIPTION

- ➤ Low pressure
- ➤ Compact with telescopic adjustment
- ➤ Can be installed into ceramic or plastic cisterns, recessed or low level cisterns, for replacement or as original equipment
- ➤ Hydraulic closure (no water hammer shock)
- ➤ Adjustable water level
- ➤ Quiet
- ➤ Anti-backflow function
- ➤ 3/8" brass, 1/2" brass and 1/2" plastic end-fitting:
 - 3/8" brass
 - flow rate: 0.21l/s at 3 bars

Pressure function range from 0.1 to 10 bars

- 1/2" brass :
- flow rate: 0.23l/s at 3 bars

Pressure function range from 0.1 to 10 bars

- 1/2" plastic :
 - flow rate: 0.22l/s at 3 bars

Pressure function range from 0.1 to 10 bars



75,5 mm max: 344 mm 538 mm, max: 344 mm

TEXT FOR TENDERS:

COMPACT 99T BP WRAS

Bottom entry inlet valve available with 1/2" & 3/8" brass connection 1/2" plastic, WRAS certified 10-year-guarantee.

Features: adjustable height, low pressure, quiet, hydraulic closure, adjustable water level and anti-back flow. Length 270mm, width 112mm, deepth 50mm.

	Ref.	Barcode	Packing	Packing			Pallet
	nei.	Darcode	Packing	Nb	M ³	Kg	quantity
COMPACT 99T BP Low Pressure 3/8" Brass	30 9922 10	3 24723 00695 38	Box	24	0.08	8.5	360
COMPACT 99T BP Low Pressure 1/2" Plastic telescopic	30 9980 10	3 24723 00712 72	Вох	24	0.08	8	360
COMPACT 99T BP Low Pressure 1/2" Brass	30 9921 10	3 24723 00695 21	Вох	24	0.08	8.5	360

